

LX3V-4PGA/LX3V-4PGB

LX3V-4PGA

Admite 4 salidas de pulsos de alta velocidad de 200 kHz. Admite aceleración y deceleración en curva T y S. Admite posicionamiento a dos velocidades y posicionamiento a una velocidad con interrupción. Admite funcionamiento a velocidad variable. Admite posicionamiento a una velocidad.

LX3V-4PGB

Admite 4 salidas de pulsos de alta velocidad de 200 kHz. Admite aceleración y deceleración en curva T. Admite posicionamiento a una velocidad.



Specification

Model	Channels	Resolution	Functionality
LX3V-4PGA	4	--	support trapezoidal / S-type acceleration and deceleration, dual-speed positioning, interrupt single-speed positioning, variable speed operation.
LX3V-4PGB	4	--	support trapezoidal acceleration and deceleration. Support single-speed positioning.

Specification

Items	LX3V-4PGA	LX3V-4PGB
Output circuit		
Power supply	DC5V ~ 30V	
Circuit insulation	Photo-coupling	
LED	LED on when Photo-coupling is driven	
Load Resistance	0.5A/ one point,0.8A/ two point	
Load Inductance	12W/DC24V	
Load Lamp	0.9W/DC24V	
Leakage current	0.1mA/DC30V	
Minimum load	--	
OFF->ON/ON->OFF	Less than 0.2ms	
Output signal	NPN	
CE Certification	CE marked	