

Model	COM	Ethernet	Monitoring	Alarm	Data Record	Validity	WVPN Pass-through	Script
V-BOX RE-00	2 in 1	1	100	20	50	60 days /1 millions	YES	YES
V-BOX RE-4G	2 in 1	1	100	20	50	60 days /1 millions	YES	YES

SPECIFICATIONS

Items	V-BOX RE-00	V-BOX RE-4G
OS		Linux
CPU		Quadcore High Performance CPU
Flash		128MB
RAM		DDRIII 64MB
SD Card		N/A
USB		OTG USB / Device USB
Serial Port		COM1: RS232, RS422 / RS485 (2 in 1)
Ethernet Port		1 Ethernet port
WIFI Modules		N/A
4G Modules	N/A	4G
Power Supply		24VDC (12~28VDC)
Power Consumption		<10W
Enclosure		Metal shell
Dimension(W*H*D)		101.0mm*73.2mm*26.8mm
Mounting Size		110.0mm*15.6mm
Weight (KG)		0.26
Vibration Resistance		IEC61131-2 Standard
Storage Temperature		-20°C~70°C
Working Temperature		-10°C~60°C
Relative Humidity		10~90% RH (Non-condensing)
CE Certification		CE marked
FCC Certification		FCC Class A
Programming		PIStudio
HTTP Interface		Yes
Remote Update		N/A
Configuration Backup		N/A
Off-line Transmission		Yes
GPS	N/A	LBS
Big Screen Display		Yes
HDMI		N/A



RE-4G MODEL FREQUENCY CODE

LTE FDD	LTE TDD
B1/B3/B5/B8	B34/B38/B39/B40/B41

Remark: Please contact us for confirmation about 4G Compatibility before purchase.

